

GASOILA® PTFE Tapes - Specialty Series



**For Oxygen
Green**



**For Gas
Yellow**



**For H2O
Pink**



**For Stainless Steel
Nickel**

FPC Stock Code	Container Size	Units per Case
GT90-24	1/2" x 260"	24
GT90	1/2" x 260"	144

- Designed for sealing oxygen based lines.
- Use on all types threaded connections.
- UL® Listed thread sealant
- Meets Mil Spec MIL-AA-58092.

FPC Stock Code	Container Size	Units per Case
YT70-24	1/2" x 260"	24
YT70	1/2" x 260"	144
YT71	1/2" x 520"	100
YT75	1" x 520"	100

- Designed for chemical installations and sealing lines carrying natural gas, propane, butane and oil.
- Use on all types of threaded connections.
- CSA® approved. UL® Listed thread sealant
- Meets MIL Spec MIL-AA-58092.

FPC Stock Code	Container Size	Units per Case
PT80-24	1/2" x 260"	24
PT80	1/2" x 260"	144

- Designed for sealing water and/or steam lines.
- Use on all types of threaded connections.
- UL® Listed thread sealant
- Meets Mil Spec MIL-AA-58092.

FPC Stock Code	Container Size	Units per Case
SA26	1/2" x 260"	40
SA26-34	3/4" x 260"	40
SA520-1	1" x 520"	40
SA260-1	1" x 260"	40
SA60	1/2" x 600"	50

- Thread Sealing Tape
- Designed for use on difficult service conditions associated with stainless steel, aluminum & brass threaded connections.
- Helps prevent seizing and galling.
- NOT for use with oxygen.
- UL® Listed thread sealant
- Meets Mil Spec MIL-T-27730A.



Density Type	Yellow	Pink/Green	Stainless
Thickness (mils)	3.8	3.7	4.3
Tensile (Min psi)	1600	1600	1000
UL Listed	Yes	Yes	Yes
MIL SPEC*	AA-58092	AA-58092	T-2773
MIL SPEC*	27730A	27730A	27730A
Density (g/cm3)	1.05 - 1.3	1.05 - 1.3	1.05 - 1.3
Elongation (%)	75	75	75
Temp. Range (°F)	-450 to +550	-450 to +550	-450 to +550
Shelf Life	Indefinite	Indefinite	Indefinite

PTFE TAPE SPECIFICATIONS

*Meets Performance Requirements of Mil Specifications Listed.



orders@federalprocess.com

Phone: 216-464-6440 | Fax: 216-464-2080 9